

Product data sheet

ECdrive T2 plus *



Automatic linear sliding door system for doors up to 140 kg
leaf weight

AREAS OF APPLICATION

- Single and double leaf sliding door systems
- Interior and exterior doors with high access frequency
- Complete solution for entrance areas with vestibule
- Opening widths from 700 to 3000 mm possible
- Door leaf weight of up to 140 kg per leaf

PRODUCT FEATURES

- Rounded cover in attractive GEZE design for highest design requirements
- With double roller carriage up to 140 kg leaf weight permitted
- Can be networked, and integrated into the building automation via open standard (BACnet)
- Freely configurable inputs and outputs for different functions
- Rechargeable battery for emergency opening and closing in case of a power failure is available as an option
- Self-cleaning roller carriage reduces maintenance work and costs
- Various mechanical and electrical locks are optionally available

TECHNICAL DATA

Productname	ECdrive T2 plus *
For 1-leaf door systems	Yes
For 2-leaf door systems	Yes
Fine-framed insulating glass	Yes
MONO glass fine-framed	Yes
Framed leaf (on site)	Yes
Wooden leaf (on site)	Yes
Depth	171 mm
Leaf weight (max.) 1-leaf	140 kg
Leaf weight (max.) 2-leaf	140 kg
Opening width 1-leaf	700 mm – 3000 mm
Opening width 2-leaf	900 mm – 3000 mm
Service temperature	-15 – 55 °C
Standard conformity	DIN 18650, EN 16005, DIN EN ISO 13849: Performance Level D

PART**DRIVE ECDRIVE T2 PLUS ***

Automatic linear sliding door drive for doors with up to 140 kg leaf weight



ECdrive T2 plus *



Designation	Ident-No.	Dimensions
Drive ECdrive T2 plus *	199122	171 mm

ECDRIVE T2 PLUS TRACK *

Track for the ECdrive T2 plus automatic sliding door system



Designation	Ident-No.	Dimensions
ECdrive T2 plus track *	200693	175 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.